

## VERSAFILLER™ WATER FOUNTAIN & BOTTLE FILLERS

Enjoy the best of both water options; refreshing fountain water and a bottle filler unit for refillable bottles. The VersaFiller™ accomplishes both tasks with ease and simplicity, and puts your location at the top of the refillable bottle trend while making a bold statement about your concern for the environment.

The VersaFiller™ is also designed for the future. The alcove and activation button contain Freshield™, which utilizes a silver-based antimicrobial compound. This is ideal for work-place settings, schools, university locations, and any public building.

The VersaFiller™ unit is available in two configurations. The **ON557** (PWSBF) model can be retrofitted to existing **OA059** (P8AC) coolers as well as Elkay's EZ8 models (some installation is required to connect this unit to existing P8AC models) providing an instant upgrade to those products already in the field.

The **ON557** (PWSBF) is also designed for simplicity of installation, requiring only water tubing connection to the host (P8), with no required electrical connections or separate drains.

The VersaFiller™ can be purchased as a complete top and bottom combination as well, **ON555** or **ON556**.

### STANDARD FEATURES:

- Waterways are lead-free in materials and construction
- Heavy-duty galvanized steel frame bolts directly to the wall
- Freshield™ antimicrobial compound
- Gauges: Panels: 22, frame: 16
- ADA compliant for adult or child when properly installed
- Certified to NSF/ANSI Standard 61, Annex G (AB1953)
- 5-year limited warranty



Model No.	Mfg. No.	Description	Capacity GPH	Dimensions					Weight lbs.	Price /Each
				W"	x	D"	x	H"		
<b>ON555</b>	PG8SBF	VersaFiller™ Combo Complete w/OA059, Sandstone Finish	8	24	x	36	x	24	74	
<b>ON556</b>	PG8SBF	VersaFiller™ Combo Complete w/OA059, Stainless Finish	8	24	x	36	x	24	74	
<b>ON557</b>	N/A	VersaFiller™ Retrofit Kit for OA059, Fountain Only (See page 1636 for OA059)	N/A	6	x	18	x	12	10	

## REPLACEMENT FILTER CARTRIDGES

**Single Action (Dirt/Rust)** - hot and cold water filters are made of pure white cellulose fibres. 1" centre hole.

**Double Action (Taste/Odour, Dirt/Rust)** - cold water only filter made of pure white cellulose fibres with activated carbon granules. For normal contamination. 1" centre hole.

**Double Action (Scale, Dirt/Rust)** - uses annular grooves and the graded density cellulose of the Dirt/Rust cartridges plus a compound to inhibit scale. Extends the life of pipes, fixtures and appliances. Cold water only. 1" centre hole.



Model No.	Filter Type	Maximum Temperature	Flow/Rate/Cartridge (GPM)	Dim H" x Dia"	Rating Microns	Price /Each
<b>NORMAL FILTRATION</b>						
<b>BA590</b>	Single (Dirt/Rust)	210°F (99°C)	6	9 3/4 x 2 5/8	5	
<b>BA592</b>	Double (Taste/Odour, Dirt/Rust)	100°F (38°C)	3	9 3/4 x 3	5	
<b>BA593</b>	Double (Scale, Dirt/Rust)	100°F (38°C)	8	9 3/4 x 2 15/16	5	
<b>HEAVY FILTRATION</b>						
<b>BA591</b>	Single (Dirt/Rust)	210°F (99°C)	6	9 3/4 x 2 5/8	50	

## ICE MAKER WATER FILTERS

- Triple action filtration provides sparkling clear ice cubes, fresh tasting water, coffee and beverages
- Protects equipment from scale and corrosion, reducing maintenance costs
- Effective taste, odor, chlorine removal
- Filters particulates as small as 5 microns
- 1/4" NPT connections, 1/2 GPM flow rate maximum



Model No.	Dimensions H" x Dia."	Max. Water Capacity	Max. Water Temperature	Pressure	Price /Each
<b>BA609</b>	8 3/8 x 2 1/4	1500 gal.	100°F (38°C)	125 PSI	

## VERSAFLOW® WATER BOTTLE FILLER RETRO-FIT KIT

- Retrofits to ADA drinking fountains as far back as 1995
- Comes complete with certified 3000 gallon lead reduction filter that treats water for the bottle filler and the fountain
- Large 13" alcove fits most large sports bottles
- Single piece polymer cabinet won't rust or dent
- Mechanical activation button dispenses water during power outages
- Large anti-microbial copper activation button is easy to push and reduces transfer of pathogens
- Filter mounted within bottle filler for easy replacement
- ADA compliant bottle filler when retrofitted to PG8AC or P8AM per manufacturer's recommendation



Model No.	Alcove Height"	Price /Each
<b>OQ915</b>	13	

## UNDER-SINK WATER FILTERS

- Compact 2 GPM cold water filter
- Filter included
- Maximum water temperature 100°F (38°C)
- 125 PSI
- Inlet/outlet size: 3/8" NPT



BA605



Model No.	Dimensions H" x Dia."	Filter Type	Filter	Wt. lbs.	Price /Each
<b>BA605</b>	8 13/16 x 4 7/8	Dirt/Rust/Taste/Odour	BA607	2 3/4	

### REPLACEMENT FILTER CARTRIDGES

Model No.	Description	For Use with Housing	Price /Each
<b>BA607</b>	Taste/Odour, Dirt/Rust	BA605	